



Disclosure to Promote the Right To Information

Whereas the Parliament of India has set out to provide a practical regime of right to information for citizens to secure access to information under the control of public authorities, in order to promote transparency and accountability in the working of every public authority, and whereas the attached publication of the Bureau of Indian Standards is of particular interest to the public, particularly disadvantaged communities and those engaged in the pursuit of education and knowledge, the attached public safety standard is made available to promote the timely dissemination of this information in an accurate manner to the public.

“जानने का अधिकार, जीने का अधिकार”

Mazdoor Kisan Shakti Sangathan

“The Right to Information, The Right to Live”

“पुराने को छोड़ नये के तरफ”

Jawaharlal Nehru


“Step Out From the Old to the New”

IS 4638 (1981): Seamless rectangular fish tins [MTD 32:
Metal Containers]

“ज्ञान से एक नये भारत का निर्माण”

Satyanaaran Gangaram Pitroda

“Invent a New India Using Knowledge”



“ज्ञान एक ऐसा खजाना है जो कभी चुराया नहीं जा सकता है”

Bhartṛhari—Nītiśatakam

“Knowledge is such a treasure which cannot be stolen”



BLANK PAGE




PROTECTED BY COPYRIGHT

IS : 4638 - 1981

Indian Standard
SPECIFICATION FOR
SEAMLESS RECTANGULAR FISH CANS
(*First Revision*)

UDC : 621.798:144:672.46 : 661.951



© Copyright 1981

INDIAN STANDARDS INSTITUTION
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG
NEW DELHI 110002

Priya P. 5.00

December 1981

Indian Standard
SPECIFICATION FOR
SEAMLESS RECTANGULAR FISH CANS
(First Revision)

Metal Containers Sectional Committee, MCPD 12

Chairman

SHRI S. M. PRADHAN

Representing

Metal Box India Ltd, Calcutta

Members

SHRI J. K. KHOSLA (*Alternate to*
Shri S. M. Pradhan)

SHRI A. K. AGARWAL Directorate of Vanaspati, Vegetable Oils & Fats,
New Delhi

DR I. A. SIDDIQI (*Alternate*)

SHRI BALBIR ONKAR SINGH Tri-sure India Ltd, Bombay

SHRI MOHAN MENON (*Alternate*)

SHRI A. K. BASU Containers and Closures Ltd, Calcutta

SHRI V. C. BHARGAVA

SHRI S. K. GHOSH (*Alternate*) Directorate of Plant Protection, Quarantine &
Storage, Faridabad

SHRI S. K. BHATIA

SHRI A. K. ANAND (*Alternate*) Directorate General of Technical Development,
New Delhi

SHRI R. H. BHATT

SHRI D. P. BHATTACHARJEE Pesticides Association of India, New Delhi
SHRI R. C. PALHAN (*Alternate*) Export Inspection Council of India, Calcutta

SHRI CHARANJIT LAL

SHRI B. R. DAVE (*Alternate*) Department of Explosives, Nagpur

SHRI A. C. CHATTRAPATE

SHRI RAJ KAPILA (*Alternate*) The Vanaspati Manufacturer's Association of India,
Bombay

SHRI M. K. DAY

SHRI U. R. SHOME (*Alternate*) M. L. Day and Co, Calcutta

SHRI M. L. DAY

SHRI P. L. DAY (*Alternate*) Day Drum Industries, Ghaziabad

SHRI DAYA NAND

Dr S. VENKATRAMAN (*Alternate*) All India Food Preservers Association (Regd),
New Delhi

SHRI V. V. GHOTGE

Balmar Lawrie & Co Ltd, Bombay

SHRI A. P. JOSEPH (*Alternate*)

SHRI M. K. JAIN Indian Oil Corporation Ltd, Bombay

SHRI M. A. MATHEW (*Alternate*)

(Continued on page 2)

© Copyright 1981

INDIAN STANDARDS INSTITUTION

This publication is protected under the *Indian Copyright Act (XIV of 1957)* and reproduction in whole or in part by any means except with written permission of the publisher shall be deemed to be an infringement of copyright under the said Act.

(Continued from page 1)

Members

SHRI P. D. KATRAK

SHRI B. KUMAR

SHRI R. KRISHNAN (*Alternate*)

SHRI A. R. MALHOTRA

MAJ-GEN M. C. S. MENON

SHRI C. G. GHOSH (*Alternate*)

SHRI T. K. GHOSH (*Alternate*)

MAJ S. K. MISRA

SHRI P. V. NARAYANAN

SHRI K. B. GUPTA (*Alternate*)

SHRI D. B. PATEL

SHRI R. K. KOUNDINYA (*Alternate*)

SHRI A. R. VIJAYENDRA RAO

SHRI P. B. RAO

SHRI V. P. AGARWAL (*Alternate*)

SHRI SAMIUL HAQUE

SHRI S. P. SHARMA

SHRI V. SAMUEL (*Alternate*)

DR K. K. SAXENA

DR S. Y. PANDIT (*Alternate*)

SHRI HARSHAD F. SHAH

SHRI D. P. CHATTERJEE (*Alternate*)

SHRI G. S. SHUKLA

SHRI P. S. DAS,

Director (MCPD)

Representing

Zenith Tin Works Ltd, Bombay

The Alkali & Chemical Corporation of India Ltd,
Calcutta

Railway Board (Ministry of Railways), New Delhi
The Tinplate Co of India Ltd, Calcutta

Ministry of Defence (DGI), New Delhi
Indian Institute of Packaging, Bombay

Poysa Industrial Co Ltd, Bombay

Central Food Technological Research Institute
(CSIR), Mysore

Steel Authority of India Ltd, New Delhi

Directorate of Weights and Measures, New Delhi

Hindustan Petroleum Corporation Ltd, Bombay

Indofil Chemicals Ltd, Thane

The Indian Paint Association, Calcutta

Directorate of Marketing and Inspection, Faridabad

Director General, ISI (*Ex-officio Member*)

Secretary

A. R. GULATI

Deputy Director (MCPD), ISI

Tinplate and Aluminium Containers Subcommittee, MCPD 12 : 2

Convener

SHRI J. K. KHOSLA

Metal Box India Ltd, Calcutta

Members

SHRI K. R. NARASIMHAN (*Alternate* to

Shri J. K. Khosla)

DR H. R. ALIMCHANDANI

Hindustan Lever Ltd, Bombay

DR N. SEN (*Alternate*)

Nestle's Products (India) Ltd, New Delhi

SHRI M. BALAN

Containers & Closures Ltd, Calcutta

SHRI A. K. BASU

SHRI P. K. MOULIK (*Alternate*)

Zenith Tin Works Ltd, Bombay

SHRI S. M. BHAGAT

SHRI P. D. KATRAK (*Alternate*)

Tinplate Fabricators Association, Calcutta

SHRI SANJAY BHATTIA

Pesticides Association of India, New Delhi

SHRI H. R. BHATT

SHRI C. C. KOTESHWARAN (*Alternate*)

(Continued on page 8)

Indian Standard

SPECIFICATION FOR
SEAMLESS RECTANGULAR FISH CANS
(First Revision)

O. FOREWORD

0.1 This Indian Standard (First Revision) was adopted by the Indian Standards Institution on 30 October 1981, after the draft finalized by the Metal Containers Sectional Committee had been approved by the Marine, Cargo Movement and Packaging Division Council.

0.2 This standard first published in 1967 has been revised to take into account the use of aluminium which is in wide use all over the world as alternate materials for the fish cans. The tolerances on the specified dimensions have also have been specified to give the manufacturers of these cans a better dimensional control in their product and to make inspection of these cans simpler. The tolerance on gross lidded capacity of the cans has also been increased to ± 5 ml instead of ± 2 ml as given in the earlier standard.

0.3 The role of the canned fish industry for consumption within the country as well as for export has been well recognized. At present fish is being canned in various types and sizes of containers and one the most commonly used, specially for sardines, is the seamless rectangular tin. This standard covers the rectangular tins only which in the trade are also known as 'Quarter Dingley Cans'. To achieve standardization of the dimensions for these containers for reasons of economy, this standard has been propogated.

0.3.1 The tins covered in this standard are intended to pack approximately 100 g of fish.

0.4 This standard contains clauses **3.4.3** and **3.6** which call for agreement between the purchaser and the supplier and which permit the purchaser to use his option for selection to suit his requirements.

0.5 For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in

accordance with IS : 2-1960*. The number of significant places retained in rounded off value should be the same as that of the specified value in this standard.

1. SCOPE

1.1 This standard prescribes the requirements for two-piece rectangular cans manufactured from tinplate or aluminium sheet used for the packing of fish.

2. TERMINOLOGY

2.1 For the purpose of this standard, the definitions given in IS : 1394-1973† shall apply.

3. REQUIREMENTS

3.1 Dimensions and Tolerances — The cans shall be manufactured to the dimensions and tolerances given in Fig. 1.

3.2 Gross Lidded Capacity — The gross lidded capacity of the can shall be between 115 ± 5 ml when measured with water at $27 \pm 2^\circ\text{C}$.

3.3 Material

3.3.1 The body of the cans shall be made from cold-reduced tinplate of deep drawing quality (TD). The tin coating for both body and the top shall be at least equivalent to D 8·4/5·6 of IS : 1993-1974‡ with a protective/decorative coating on the external surface.

3.3.2 The nominal thickness of the tinplate used shall be 0·25 mm.

3.3.3 The body and top of the cans may be made from aluminium alloy sheet conforming to Grade 31000 or to 52000 of IS : 737-1974§. The minimum thickness of the aluminium sheet be 0·27 mm.

3.4 Manufacture

3.4.1 Each component shall be manufactured from a single piece of metal.


3.4.2 The body shall be manufactured as shown in Fig. 1.

*Rules for rounding off numerical values (*revised*).


†Glossary of terms relating to metal containers (*second revision*).

‡Specification for cold-reduced tinplate and cold-reduced blackplate (*first revision*).

§Specification for wrought aluminium and aluminium alloys, sheet and strip (for general engineering purposes) (*second revision*).



TOP VIEW OF TIN AFTER SEAMING



All dimensions in millimetres.


FIG. 1 SEAMLESS RECTANGULAR FISH CAN

3.4.3 The tops shall be scored and shall be provided with a tongue for the purpose of opening the can as shown in top view of Fig. 1. Details of the tongue have been shown in Fig. 2. If required by the purchaser, the top may be provided with stiffening ribs.

3.4.4 The end seams shall be lined with a suitable non-toxic compound and shall be double seamed.

3.4.5 The key for opening the can may be supplied loose or fixed, in any manner to the top. A typical key of galvanized steel wire is shown in Fig. 3. The wire used shall have a diameter of not less than 3.25 mm.

3.4.6 The cans shall be new and in a clean condition inside and outside and shall be free from rust and foreign matter.



Tolerance on all dimensions ± 0.1 mm.

All dimensions in millimetres.

FIG. 2 DETAILS OF TONGUE

Tolerance on all dimensions ± 0.1 mm

All dimensions in millimetres.

**FIG. 3 DIMENSIONS OF KEY FOR
OPENING THE CAN**

3.5 Internal Finish — The internal surface of the tinplate can may be uniformly lacquered with a suitable non-toxic lacquer.

3.6 External Treatment — The external surface of the cans may be given a decorative and/or protective coating, if agreed to between the purchaser and the supplier.

3.7 Air Pressure Test — The can with the top seamed on shall be capable of withstanding an internal air pressure of 70 kPa without any signs of leakage when tested in water.

4. MARKING

4.1 The manufacturer's name, initials or recognized trade-mark and the year of manufacture may be clearly and indelibly marked or embossed on the can in such a manner that the marking shall not lead to any contamination or deterioration of the product packed in the container, or any damage to the container.

4.1.1 The cans may also be marked with the ISI Certification Mark.

NOTE — The use of the ISI Certification Mark is governed by the provisions of the Indian Standards Institution (Certification Marks) Act and the Rules and Regulations made thereunder. The ISI Mark on products covered by an Indian Standard conveys the assurance that they have been produced to comply with the requirements of that standard under a well-defined system of inspection, testing and quality control which is devised and supervised by ISI and operated by the producer. ISI marked products are also continuously checked by ISI for conformity to that standard as a further safeguard. Details of conditions under which a licence for the use of the ISI Certification Mark may be granted to manufacturers or processors may be obtained from the Indian Standards Institution.

(Continued from page 2)

Members

SHRI K. R. DAS	India Paint Association, Calcutta
SHRI S. K. GUPTA	Ministry of Defence (DGI), New Delhi
SHRI M. L. DHUPER (<i>Alternate</i>)	Indian Aluminium Co Ltd, Calcutta
SHRI A. K. HAJRA	
SHRI P. CHAKRAVORTY (<i>Alternate</i>)	Bharat Containers Pvt Ltd, Bombay
SHRI HEMANT KANORIA	Vanaspati Manufacturer's Association of India, Bombay
SHRI RAJ KAPILA	The Alkali & Chemical Corporation of India Ltd, Hyderabad
SHRI B. KUMAR	
SHRI V. K. MATHUR (<i>Alternate</i>)	
MAJ-GEN M. C. S. MENON	Tinplate Co of India Ltd, Jamshedpur
DR S. Y. PANDIT	Bayer (India) Ltd, Thane
Dr P. V. RAIKER (<i>Alternate</i>)	Poysa Industrial Co Ltd, Bombay
SHRI D. B. PATEL	
SHRI S. P. BANERJEE (<i>Alternate</i>)	Extrusion Processes Pvt Ltd, Bombay
SHRI N. M. PATEL	
SHRI K. M. PATEL (<i>Alternate</i>)	Steel Authority of India Ltd, Rourkela
SHRI V. P. SARDANA	
SHRI V. P. AGARWAL (<i>Alternate</i>)	Hindustan Petroleum Corporation Ltd, Bombay
SHRI S. P. SARMA	
SHRI N. SETHURAMAN (<i>Alternate</i>)	Klas Engineering Pvt Ltd, Bangalore
SHRI K. L. V. SUBBIAH	Directorate of Marketing & Inspection (Ministry of Rural Reconstruction), Faridabad
SHRI S. RAMAN (<i>Alternate</i>)	Indian Oil Corporation Ltd, Bombay
SHRI G. S. SHUKLA	Directorate of Vanaspati, Vegetable Oils & Fats, New Delhi
SHRI M. K. SHUKLA	Lallubhai Amichand Ltd, Bombay
DR I. A. SIDDIQI	
SHRI V. S. THAKKAR	
SHRI C. B. SHAIIL (<i>Alternate</i>)	
SHRI N. M. SHAH (<i>Alternate</i>)	

Representing

INTERNATIONAL SYSTEM OF UNITS (SI UNITS)

Base Units

QUANTITY	UNIT	SYMBOL
Length	metre	m
Mass	kilogram	kg
Time	second	s
Electric current	ampere	A
Thermodynamic temperature	kelvin	K
Luminous intensity	candela	cd
Amount of substance	mole	mol

Supplementary Units

QUANTITY	UNIT	SYMBOL
Plane angle	radian	rad
Solid angle	steradian	sr

Derived Units

QUANTITY	UNIT	SYMBOL	DEFINITION
Force	newton	N	1 N = 1 kg.m/s ²
Energy	joule	J	1 J = 1 N.m
Power	watt	W	1 W = 1 J/s
Flux	weber	Wb	1 Wh = 1 V.s
Flux density	tesla	T	1 T = 1 Wb/m ²
Frequency	hertz	Hz	1 Hz = 1 c/s (s ⁻¹)
Electric conductance	siemens	S	1 S = 1 A/V
Electromotive force	volt	V	1 V = 1 W/A
Pressure, stress	pascal	Pa	1 Pa = 1 N/m ²

INDIAN STANDARDS INSTITUTION

Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW DELHI 110002

Telephones : 26 60 21, 27 01 31

Telegrams : Manaksanstha

Telephone

Regional Offices:
 Western : Novelty Chambers, Grant Road
 Eastern : 5 Chowinghee Approach
 Southern : C. I. T. Campus, Adyar
 Northern : B69, Phase VII

BOMBAY 400007	37 97 29
CALCUTTA 700072	27 50 90
MADRAS 600020	41 24 42
S.A.S. NAGAR (MOHALI) 160051	—

Branch Offices:

'Pushpak', Nurmohamed Shaikh Marg, Khanpur	AHMADABAD 380001	2 03 91
'F' Block, Unity Bldg, Narasimharaja Square	BANGALORE 560002	2 76 49
Gangotri Complex, Bhadbhada Road, T.T. Nagar	BHOPAL 462003	6 27 16
22E Kalpana Area	BHUBANESHWAR 751014	5 36 27
5-8-56C L. N. Gupta Marg	HYDERABAD 500001	22 10 83
R 14 Yudhister Marg, C Scheme	JAIPUR 302005	6 98 32
117/418-B Sarvodaya Nagar	KANPUR 208005	4 72 92
Patliputra Industrial Estate	PATNA 800013	6 28 08
Hantex Bldg (2nd Floor), Rly Station Road	TRIVANDRUM 695001	32 27